

UL PRODUCT CATEGORY

Gypsum Board

See General Information for Gypsum Board

THAI GYPSUM PRODUCTS PCL

R27517

539/2 Gypsum Metropolitan Tower
Si Ayuthaya Rd., Ratchathewi
Bangkok, 10400 THAILAND

5/8 in. thick, 24 to 48 in. wide, Type X for use in Design Nos. **N505, N602, U305, U379, X501, X509, X517, X528, X602, X604.**

5/8 in. thick, 46 to 54 in. wide, Type X for use in Design Nos. **L501, N502, N505, U301, U302, U305, U354, U379, U396, U411, U421, U501, V419, X501, X509, X517, X525, X526, X527, X528, X602, X604.**



5/8 in. thick, 48 in. wide, Type X for use in Design Nos. **G501, G503, G505, G507, G508, G510, G520, G528, L501, L508, L591, N501, N502, N505, N602, P227, U017, U026, U301, U302, U305, U309, U326, U330, U338, U339, U341, U342, U344, U354, U355, U356, U376, U379, U391, U396, U405, U411, U417, U418, U420, U421, U425, U434, U442, U445, U460, U465, U487, U494, U501, U502, U504, U505, U506, U510, U512, U513, U615, V313, V314, V332, V417, V419, V434, V437, V463, V469, W409, W437, W452, X501, X509, X517, X525, X526, X527, X528, X602, X604.**

1/2 in. thick, 48 in. wide, Type C for use in Design Nos. **G502, G504, G515, G523, G524, G526, G527, G528, G529, G530, G531, G533, G534, G552, K912, L502, L503, L504, L506, L507, L509, L510, L512, L514, L517, L518, L519, L524, L525, L530, L535, L537, L542, L580, L587, P237, P506, P510, P512, U312, U313, U317, U319, U320, U403, U406, U410, U412, U418, U425, U426, U428, U429, U435, U436, U438, U440, U441, U443, U444, U448, U451, U452, U453, U454, U455, U462, U463, U467, U474, U478, U497, U512, U529, U608, U620, U910, U912, U914, V418, W409, W437, X404, X507, X513, X514, X515, X518, X520, X521, X522, X523, X524, X525, X526, X528, X530, X531, X533, X534.**

5/8 in. thick, 48 in. wide, Type C for use in Design Nos. **D301, D501, D502, D504, D505, G501, G503, G505, G507, G508, G509, G510, G512, G515, G520, G521, G523, G525, G526, G527, G528, G529, G531, G538, G561, G568, G601, J501, J503, J504, K912, L501, L505, L508, L511, L512, L513, L514, L515, L516, L520, L523, L525, L526, L528, L529, L530, L533, L534, L535, L536, L537, L538, L539, L540, L557, L562, L588, L591, L601, N501, N502, N505, P227, P503, P504, P505, P506, P507, P508, P509, P510, P512, P513, P514, P519, P538, P556, U017, U023, U301, U302, U305, U309, U311, U313, U319, U329, U331, U333, U334, U340, U341, U342, U344, U354, U355, U356, U376, U379, U396, U403, U405, U411, U418, U420, U421, U425, U428, U429, U436, U442, U445, U451, U457, U465, U466, U467, U469, U473, U485, U501, U502, U504, U505, U506, U510, U512, U513, U528, U602, U605, U615, U617, U622, U623, U626, U627, U633, U637, U642, U643, U645, V305, V314, V332, V414, V419, V431, V434, V437, V463, V469, V495, W409, W437, W451, W452, X501, X502, X504, X508, X509, X516, X517, X525, X526, X527, X528, X602, X604.**

5/8 in. thick, 4 ft wide, 5/8" Type X for use in Design Nos. U017, U301, U302, U305, U309, U326, U330, U332, U337, U338, U339, U341, U342, U354, U355, U357, U358, U360, U411, U418, U420, U421, U425, U434, U442, U445, U460, U465, U466, U467, U473, U475, U487, U494, U501, U502, U504, U505, U506, U510, U512, U615, U617, U622, U623, U626, V417, V419, V434, W452, X508, X516, X517, X525, X526, and X528.

1 in. thick, 24 in. wide, Type Shaftliner for use in Design Nos. U366, U417, U428, U429, U529, W409, W437.

Trademark and/or Tradename:  or  .

Last Updated on 2019-05-22

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2019 UL LLC".

UL and the UL logo are trademarks of UL LLC © 2019 All Rights Reserved.